05 THREE-WHEEL ELECTRIC FORKLIFT

EFS151
–Capacity 1.5T
–Lifting Height 3000mm
–Max. Lifting Height 4500mm
–48V/150Ah Li-ion
48V/180Ah AGM
–AC Controller
–Integrated charger

CPD15/18/20TVL
–Capacity: 1.5/1.8/2.0T
–Lifting Height: 3000mm
–Max Lifting Height: 5500/6000mm
–80V/150Ah/205Ah
–AC Controller
–Drive motor: dual
–Integrated charger

TDL201
–Capacity 2.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–48V/405Ah
–AC Controller
–Integrated charger

06 FOUR-WHEEL ELECTRIC FORKLIFT

EFL181
–Capacity 1.8T
–Lifting Height 3000mm
–Max. Lifting Height 4800mm
–48V/150Ah/205Ah
–AC drive/DC lift
–Drive Motor: single
–Integrated charger

EFL201
–Capacity 2.0t
–Lifting Height 3000mm
–Max Lifting Height 4800mm
–80V/150Ah/205Ah/280Ah
–AC Controller
–Optional integrated charger

CPD15/20L1
–Capacity 1.5/2.0T
–Lifting Height 3000mm
–Max. Lifting Height 5000mm
–48V/405Ah
–AC Controller

CPD20L1S
–Capacity 2.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–48V/405Ah
–AC Controller
–Drive Motor: single

ICE251
–Capacity 2.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/205Ah/280Ah/410Ah
–AC Controller
–Optional integrated charger

ICE301/351
–Capacity 3.0/3.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/205Ah/280Ah/410Ah
–AC Controller
–Optional integrated charger

CPD30/35L1S
–Capacity 3.0/3.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/560Ah
–AC Controller

CPD18/20FVL
–Capacity 1.8/2.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/205Ah
–AC Controller
–Drive motor: dual
–Integrated Charger

CPD25L2S
–Capacity 2.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/560Ah
–AC Controller
–Drive Motor: dual

EFL253/303/353(S/P)
–Capacity 2.5/3.0/3.5T
–Lifting Height 3000mm
–Max Lifting Height 6000mm
–80V/205Ah/230Ah/280Ah
410Ah/460Ah/560Ah
–AC Controller

EFX251
–Capacity 2.5T
–Lifting Height 3000mm
–Max. Lifting Height 5000mm
–80V/150Ah
–AC Controller
–Drive Motor: single
–Integrated charger

EFX302
–Capacity 3.0T
–Lifting Height 3000mm
–Max Lifting Height 4800mm
–80V/100Ah/150Ah/205Ah/230Ah
–PMSM Controller

CPD45/50F8
–Capacity 4.5/4.99T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm
–80V/700Ah/560Ah(Li-ion)
–AC Controller
–Drive Motor: single

EFL702/EFL1002
–Capacity 7.0/10.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000/6030mm
–80V/820Ah/1230Ah
–AC Controller

EFL1602/1802
–Capacity 16.0/18.0T
–Lifting Height 3000mm
–Max Lifting Height 4200mm
–614.4V/230Ah
–AC Controller

EP EQUIPMENT CO., LTD info@ep-ep.com

07 DIESEL FORKLIFT

MAX-8
CPCD15-35T8
CPQD30-35T8
–Capacity 1.5/1.8/2.0/2.5/3.0/3.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm

MAX-8
CPCD45T8
CPCD50T8-X
–Capacity 4.5/5.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm

MAX-8
CPCD50/60/70T8
–Capacity 5.0/6.0/7.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm

CPCD80/100T8
–Capacity 8.0/10.0T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm

08 LPG FORKLIFT

MAX-8
CPQ(Y)D15/18/20 /25/30/35T8
–Capacity 1.5/1.8/2.0/2.5/3.0/3.5T
–Lifting Height 3000mm
–Max. Lifting Height 6000mm

NO.121YongHua Street,Shi Qiao Road, Xia Cheng Qu,Hangzhou,China
Tel:86-571-28035656/28878695 Fax:86-571-28035665
E-mail:info@ep-ep.com www ep-ep.com

EP EQUIPMENT CO., LTD info@ep-ep.com

Let's grow together

V2302.01

EPAustralia

PRODUCT OVERVIEW

INTRODUCTION

At EP Equipment we strive to make the world of material handling greener and smarter. We believe in growing together with a network of partners to create a real benefit for the customer. Lithium Ion technology is the technology to change the material handling industry and it should be accessible for everyone at a reasonable price.
Let's change the world together. One truck at a time.

EP EQUIPMENT CO., LTD
ep-ep.com

EP WAREHOUSE EQUIPMENT

01 ELECTRIC PALLET TRUCK

MINI
EPT12-EZX
–Capacity 1.2T
–Fork Width 560/685mm
–Fork Length 1150mm
–24V/20Ah Lithium
–Travel Speed 4/4.5km/h
–DC Controller

MINI
F1
–Capacity 1.5T
–Fork Width 685/560mm
–Fork Length 1150mm
–24V/65Ah
–Travel Speed 4.5km/h
–DC Controller

NEW CE

MINI
F2
–Capacity 1.5T
–Fork Width 685/560mm
–Fork Length 1150mm
–24V/20Ah
–Travel Speed 4.5km/h
–DC Controller

LiST CE NEW

MINI
F3
–Capacity 1.5T
–Fork Width 685/560mm
–Fork Length 1150mm
–24V/20Ah
–Travel Speed 4.5km/h
–DC Controller

LiST CE NEW

MINI
F4
–Capacity 1.5T
–Fork Width 685/560mm
–Fork Length 1150mm
–24V/20Ah
–Travel Speed 4.5km/h
–DC Controller

LiST NEW CE

MINI
EPL153(1)
–Capacity 1.5T
–Fork Width 560/685mm
–Fork Length 1150mm
–24V/20Ah
–Travel Speed 5.0km/h
–DC Controller

LiST CE

MINI
EPL154
–Capacity 1.5T
–Fork Width 540/685mm
–Fork Length 1150mm
–24V/30Ah
–Travel Speed 5.0km/h
–DC Controller

LiST CE

MINI
EPL185
–Capacity 1.8T
–Fork Width 540/685mm
–Fork Length 1150mm
–48V/20Ah
–Travel Speed 5.5km/h
–DC Controller

LiST CE

MINI
F4 201
–Capacity: 2.0T
–Fork Width: 685/560mm
–Fork Length: 1150mm
–48V/20Ah
–Travel Speed: 4.5/5 km/h
–BLDC Controller

LiST NEW

MAX
WPL201
–Capacity 2.0T
–Fork Width 540/685mm
–Fork Length 1170mm
–48V/30Ah
–Travel Speed 5.5km/h
–DC Controller

LiST

MAX
WPL202
–Capacity 2.0T
–Fork Width 540/685mm
–Fork Length 1150mm
–24V/100Ah
–Travel Speed 5.5/6 km/h
–AC Controller

LiST CE

MAX
KPL201
–Capacity 2.0T
–Fork Width 540/685mm
–Fork Length 1150mm
–24V/205Ah
–Travel Speed 10km/h
–AC Controller

LiST CE

MAX
RPL201(H)
–Capacity 2.0T
–Fork Width 540/685mm
–Fork Length 1150/1220mm
–24V/205Ah
–Travel Speed 8.0/12 km/h
–AC Controller

LiST CE

MAX
RPL251/301
–Capacity 2.5/3.0T
–Fork Width 560/685mm
–Fork Length 1150/1220mm
–24V/205Ah
–Travel Speed 6.0km/h
–AC Controller

LiST CE

MINI
EPT20-15ET
–Capacity 1.5T
–Fork Width 560/685mm
–Fork Length 1150mm
–24V/85Ah
–Travel Speed 4.5km/h
–DC Controller

CE

MINI
EPT20-15ET2
–Capacity 1.5T
–Fork Width 560/685mm
–Fork Length 1150mm
–24V/65Ah/85Ah(Li–ion)
–Travel Speed 5.0km/h
–DC Controller

LI-ION CE

MINI
EPT20-18EA
–Capacity 1.8T
–Fork Width 540/645/685mm
–Fork Length 1150mm
–24V/85Ah
–Travel Speed 5.0km/h
–AC Controller

MINI
EPT20-ET
–Capacity 2.0T
–Fork Width 560/685mm
–Fork Length 1150mm
–48V/30Ah
–Travel Speed 5.5km/h
–DC Controller

CE

MINI
EPT20-ET2(L)
–Capacity 2.0T
–Fork Width 560mm
–Fork Length 1150mm
–48V/30Ah(AGM)/48V/20Ah(Li–ion)
–Travel Speed 5.5km/h
–DC Controller

LI-ION NEW

MAX
EPT20-20WA
EPT25-WA
–Capacity 2.0/2.5T
–Fork Width 540/685mm
–Fork Length 1150/1220mm
–24V/210Ah/240Ah/205Ah(Li–ion)
–Travel Speed 5.5km/h
–AC Controller

LI-ION CE

MAX
EPT20-30RTS
EPT20-35RTS
–Capacity 3.0/3.5T
–Fork Width 686mm
–Fork Length 1190mm
–24V/280Ah/360Ah
–Travel Speed 12km/h
–AC Controller

02 ELECTRIC STACKER

MINI
ESD122
–Capacity 1.2T
–Lifting Height 2490mm
–Max. Lifting Height 3590mm
–24V/85Ah
–DC Controller

MINI
ES12-25MM
ES12-25DM
–Capacity 1.2T
–Lifting Height 1510/2980mm
–Max. Lifting Height 1920/3780mm
–24V/85Ah/105Ah/125Ah/
80Ah(Li–ion)
–DC Controller

LI-ION CE

MAX
ES12-25WA
–Capacity 1.2T
–Lifting Height 3280mm
–Max. Lifting Height 5000mm
–24V/210Ah/205Ah(Li–ion)
–AC Controller

LI-ION CE

MAX
ES12-12CS
ES15-15CS
–Capacity 1.2/1.5T
–Lifting Height 3270/3200mm
–Max. Lifting Height
4500mm/5000mm
–24V/210Ah/280Ah/
205Ah(Li–ion)
–AC Controller

LI-ION

MAX
ES14-30WA
ES18-40WA
–Capacity 1.4/1.8T
–Lifting Height 3200mm
–Max. Lifting Height 5000mm
–24V/210Ah/280Ah/205Ah(Li–ion)
–AC Controller

LI-ION CE

MINI
ES15-33DM
–Capacity 1.5T
–Lifting Height 3280mm
–Max. Lifting Height 3590mm
–24V/125Ah
–AC Controller

03 TOW TRACTOR&ORDER PICKER

MAX
JX0
–Capacity 90/110/136KG
–Lifting Height 3000mm
–24V/120Ah/135Ah(Li–ion)
–DC Controller

LI-ION CE

MAX
JX1
–Capacity 227/137/136KG
–Lifting Height 3200mm
–Max. Lifting Height 4880mm
–24V/224Ah/280Ah/205Ah(Li–ion)
–Travel Speed 5.5km/h
–AC Controller

LI-ION CE

MINI
QDD10
–Capacity 1.0T
–Travel Speed 5.0km/h
–24V/50Ah
–DC Controller

CE

MINI
QDD10L
–Capacity 1.0T
–Travel Speed 5.0km/h
–24V/20Ah
–DC Controller

LiST CE

MINI
QDD10/15T
–Capacity 1.0/1.5T
–Travel Speed 5.0km/h
–24V/20Ah
–DC Controller

LiST

MAX
QDD30S/QDD45S
–Capacity 3.0/4.5T
–Travel Speed 7.0km/h/5.0km/h
–24V/210Ah/280Ah
–AC Controller

MAX
QDD301T/601T
QDD301T/601T
–Capacity 3.0/6.0T
–Travel Speed 15.0/17.0km/h
–48V/240Ah/275Ah/280Ah(Li–ion)
–AC Controller

LI-ION NEW CE

MAX
EPT20-RAP
–Capacity 2.0T
–Fork Width 540/600/685mm
–Fork Length 1150mm
–24V/360Ah/205Ah(Li–ion)
–Travel Speed 12km/h
–AC Controller

LI-ION CE

04 REACH TRUCK

MAX (Walkie Reach Stacker)
CQE15S
–Capacity 1.5T
–Lifting Height 3000mm
–Max. Lifting Height 5500mm
–24V/280Ah/205Ah(Li–ion)
–AC Controller

LI-ION CE

MAX
CQD16L
–Capacity 1.6T
–Lifting Height 6500mm
–Max. Lifting Height 8000mm
–48V/405Ah
–AC Controller

LiST

MAX
CQD20L
–Capacity 2.0T
–Lifting Height7500mm
–Max. Lifting Height 12000mm
–48V/405Ah
–AC Controller

LiST CE

MAX
CQD16/20RV(F)2
–Capacity 1.6/2.0T
–Lifting Height 7500mm
–Max. Lifting Height 12000mm
–48V/500Ah/405Ah(Li–ion)
–AC Controller

LI-ION

MAX
CQD25RV(F)
–Capacity 2.5T
–Lifting Height 12000mm
–Max. Lifting Height 125000mm
–48V/700Ah
–AC Controller

NEW